

Duct tape C3356

Product Description

C3356 is a hot-melt cloth pressure sensitive adhesive tape, beautiful appearance, strong adhesion, high tensile strength, can be used for items fixed, surface protection, etc.

Product Features

- Good initial tack.
- With beautiful appearance, can produce various color products according to demand

Main applications

- Carton sealing, surface protection.
- Binding, fixing, construction and repairing

Usage guidelines

- Surfaces to which tape is applied should be clean, dry and free of grease, oil, moisture, dirt and other contaminants.
- Sufficient pressure should be applied during application. It will affect the properties and appearance if the pressure is not enough.
- The tape is designed for indoor use. Exposure to sunlight may cause tape more difficult to remove.

Storage condition

- Shelf life: 9 months from date of production. Tape should be stored in a cool (temperature between 10°C ~35°C), dry (humidity below 50%) environment.
- Well ventilated area away from sunlight, air conditioner and other heat sources.

Product composition

Substrate:	Cloth and PE
Adhesive:	hot melt

Product Properties

	Spec.
Total thickness (mm) ASTM D-3652	0.220±0.01
Initial tack (mm) PSTC-6	≤50
Peel adhesion(OZ./in) ASTM D-3330	≥36(10N/25mm)
Holding power (hrs/1kg) PSTC-107	≥2.0
Tensile strength (lbs/in) ASTM D-3759	≥20(38N/cm)

Note: The data are only typical properties based on ASTM standard test, they are not equal with the normal instruction.

Specification

Jumbo roll size: 1060mm X 1250m

Finish roll size: as per customer's requirement

For details please contact with our sales.